

KR20S

YewdaleKestrel® Slow-rise spring

yewdaleKestrel®
MAGNETIC ANTI-LIGATURE SYSTEM



KR20S Slow-rise spring

Features:

The YewdaleKestrel® KR20S spring roller blind with a brake to ensure a slow, smooth and quiet operation. White metal universal brackets fitted to white aluminium back bar for face, top or side fixing with 32mm grooved aluminium barrel. Fabric is locked into a groove in the barrel, and features a white tear drop aluminium bottom bar with cord pull as standard. This system uses magnetic wall-fix/top-fix brackets. This ensures that, under excess load, the back bar separates from the bracket leaving no remaining points of ligature.

Benefits:

Smooth and quiet operation makes the KR20S an excellent choice for a vast range of applications. The KR20S braked spring blind provides the ultimate cord/chain-free solution and offers exceptional ease of use. The slow-rise spring is enclosed within the barrel and supported by sturdy, attractive metal brackets. Fitted to white aluminium back bar and secured by magnetic brackets for 100% fail-safe* anti-ligature functionality. Fabric is locked into the barrel and bottom bar maintaining exceptional edge to edge coverage for even better shading properties.

Options:

Spring limit stop; Alternative bottom bars, including fully fabric covered, in aluminium or plastic, and aluminium Tear Drop in black or silver.

Specification:

The magnetic anti-ligature YewdaleKestrel® KR20S braked spring control roller blind with vandal resistant, cord/chain-free braked spring as manufactured by Yewdale, +44 (0)1268 570900. Flame retardant fabric from the YewdaleDefiant® range, locked into grooved 32mm aluminium barrel along with white Tear Drop aluminium bottom bar. Slow-rise spring and braked spring end housed within aluminium barrel supported by white metal brackets, and fitted to white aluminium back bar, secured by magnetic wall-fix/top-fix brackets spaced in accordance with

manufacturer's recommendations. Fitting to be carried out by trained and accredited personnel.

O+M Guidance

It is an NHS requirement that items suspended on load-release support systems should be maintained and load-tested in accordance with the manufacturer's instructions on an annual basis. The YewdaleKestrel® system's performance remains constant even after repeated use. It is a requirement, however, to carry out a physical inspection and testing of YewdaleKestrel® fittings to identify any possible damage or evidence of tampering and undertake an annual load test. Annual testing should only be carried out by Protects Plus 0345 646 0955.

YewdaleKestrel® KR20S is the only approved braked spring roller blind system to be used with YewdaleKestrel®

Roller Blinds Specification Guide

Roller blinds	Min Width*	Max Width	Max Drop	Max M ²
KR20S**	450	1850	2450	4.3

Sizes shown in millimetres. Based on fabric weight of 220g/m², e.g. Thames. Use of heavier fabrics may require appropriate reductions. *Where adjacent blinds are fitted with YewdaleKestrel®, there should be no more than 2 brackets within a total distance of 700mm. **Use of limit stop may require appropriate reductions.



Find this product on NBS Source



This product range comes with a full Lifetime Warranty as standard.

yewdale.co.uk
see things differently

Call: +44 (0)1268 570900 Fax: +44 (0)1268 732509 Email: sales@yewdale.co.uk
Yewdale, Enterprise Way, Wickford, Essex, SS11 8DH | 4 Sutton Lane, London, EC1M 5PU